

**What is claimed is:**

1. A mass spectrometer adapted for underwater use comprising:  
a watertight case having an inlet;  
means for transforming an analyte molecule from a solution phase into a gas  
5 phase positioned within the case;  
means for directing a fluid to the transforming means from the inlet; and  
a linear quadrupole mass filter for analyzing the gas-phase analyte molecule  
to determine an identity thereof.

10 2. The mass spectrometer recited in Claim 1, wherein the transforming means  
comprises an introduction probe comprising a membrane having selective transport  
properties, the membrane positioned between the directing means and the analyzing  
means.

15 3. The mass spectrometer recited in Claim 2, wherein the membrane has  
selective transport properties for nonpolar compounds.

4. The mass spectrometer recited in Claim 3, wherein the membrane comprises  
polydimethylsiloxane.

20 5. The mass spectrometer recited in Claim 3, further comprising means for  
regulating a temperature of the fluid along the directing means.

6. The mass spectrometer recited in Claim 1, further comprising a first reservoir for holding a control fluid, and wherein the directing means comprises a pump having means for selectively directing fluid from the first reservoir to the transforming means.

5 7. The mass spectrometer recited in Claim 1, wherein the analyzing means further comprises a computer in electronic communication with the mass filter for controlling data acquisition of the mass filter and for performing analysis of data collected by the mass filter.

10 8. The mass spectrometer recited in Claim 1, further comprising a housing surrounding the mass filter and a pump for providing a vacuum within the mass filter housing.

15 9. The mass spectrometer recited in Claim 8, wherein the pump comprises a turbo-molecular drag pump and two diaphragm pumps connected in series.

10. The mass spectrometer recited in Claim 9, further comprising means for dissipating heat generated by the pump.

20 11. The mass spectrometer recited in Claim 10, wherein the heat dissipating means comprises a heat sink plate in thermal contact with a heat-conducting material in contact with the case.

12. The mass spectrometer recited in Claim 1, further comprising a means for creating and maintaining a vacuum within the analyzing means in the watertight case.

13. The mass spectrometer recited in Claim 1, wherein the watertight case comprises a first and a second watertight cases, the transforming means and the analyzing means residing in the second case, and the directing means residing in the first case.

14. The mass spectrometer recited in Claim 1, wherein the transforming means comprises an atmospheric pressure ionization device.

15. The mass spectrometer recited in Claim 14, wherein the pressure ionization device comprises an electrospray ionization device.

16. The mass spectrometer recited in Claim 14, further comprising a third watertight case and a pump for creating a vacuum within the analyzing means, the pump positioned within the third case.

17. A modular, submersible mass spectrometry system comprising a plurality of sealed, substantially fluid-tight pressure vessels for operating in an aqueous environment, the system comprising:

a fluidic control pressure vessel containing:

an inlet from and an outlet to an exterior of the flow injection pressure vessel; and

a pump in fluid communication with a control fluid and a sample fluid having a means for selectively pumping the control fluid and the sample fluid to the outlet;

a mass spectrometer pressure vessel containing:

an introduction probe in fluid communication with the fluidic control pressure vessel outlet for transforming an analyte gas molecule present in fluid therefrom comprising a membrane having selective transport properties for nonpolar volatile compounds, the introduction probe for transforming an analyte gas molecule present in fluid from the fluid control pressure vessel outlet from a solution phase into a gas phase;

a fluid line for establishing fluid communication between the fluidic control pressure vessel outlet and the introduction probe;

a linear quadrupole mass filter in fluid communication with the introduction probe for collecting data on the gas-phase analyte molecule; and

data analysis means for receiving the data collected by the mass filter and performing an analysis thereof to determine an identity of the gas-phase analyte molecule;

a roughing pump pressure vessel containing a vacuum pump for providing low-pressure conditions in the mass filter; and

a line connecting the vacuum pump with the mass filter.

**18.** The system recited in Claim 17, wherein the introduction probe membrane comprises polydimethylsiloxane.

19. The system recited in Claim 17, further comprising means for regulating a temperature of the fluid pumped to the introduction probe.

20. The system recited in Claim 17, wherein the data analysis means comprises a computer in electronic communication with the mass filter having software resident thereon for controlling data acquisition of the mass filter and for performing analysis of data collected by the mass filter.

21. The system recited in Claim 17, wherein the vacuum pump comprises two diaphragm pumps connected in series, and further comprising a turbo-molecular drag pump housed within the mass spectrometer vessel and in communication with the line between the two diaphragm pumps and the mass filter.

22. The system recited in Claim 17, further comprising means for dissipating heat generated by the vacuum pump.

23. The system recited in Claim 22, wherein the heat dissipating means comprises a heat sink plate positioned within the pump vessel in thermal contact with a heat-conducting material in contact with the pump vessel.

24. A method for identifying a molecule in an aqueous environment comprising the steps of:

directing a fluid into a substantially fluid-tight case;

transforming an analyte molecule in the fluid from a solution phase into a gas phase within the case; and

analyzing the analyte molecule using a linear quadrupole mass filter to determine an identity thereof.

5

**25.** The method recited in Claim 24, wherein the transforming step comprises using an introduction probe comprising a membrane having selective transport properties for nonpolar volatile compounds.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

**26.** The method recited in Claim 25, wherein the membrane comprises polydimethylsiloxane.

**27.** The method recited in Claim 24, further comprising regulating a temperature of the fluid directed to the introduction probe.

**28.** The method recited in Claim 24, wherein the directing step comprises selectively directing fluid from each of a control fluid source and a sample fluid source to the introduction probe.

20

**29.** The method recited in Claim 24, wherein the analyzing step further comprises using a computer in electronic communication with the mass filter for controlling data acquisition of the mass filter and for performing analysis of data collected by the mass filter.

**30.** The method recited in Claim 24, further comprising providing a vacuum within a housing surrounding the mass filter.

**31.** The method recited in Claim 30, wherein the pumping step comprises using a turbo-molecular drag pump and two diaphragm pumps connected in series.

**32.** The method recited in Claim 24, further comprising dissipating heat generated by the pump.

**33.** The method recited in Claim 32, wherein the heat dissipating step comprises using a heat sink plate in thermal contact with a heat-conducting material in contact with the case.

**34.** A method for making a mass spectrometer adapted for underwater use comprising the steps of:

positioning a means for transforming an analyte molecule from a solution phase into a gas phase within a watertight case having an inlet;

positioning a means for directing a fluid to the transforming means from the inlet within the case; and

positioning a linear quadrupole mass filter for analyzing the gas-phase analyte molecule to determine an identity thereof within the case.

35. The method recited in Claim 34, wherein the transforming means comprises an introduction probe comprising a membrane having selective transport properties for nonpolar volatile compounds, the membrane positioned between the directing means and the analyzing means.

5

36. The method recited in Claim 35, wherein the membrane comprises polydimethylsiloxane.

37. The method recited in Claim 34, further comprising the step of positioning a means for regulating a temperature of the fluid along the directing means within the case.

38. The method recited in Claim 34, further comprising the step of positioning a first reservoir for holding a control fluid and a second reservoir for holding waste fluid within the case, and wherein the directing means positioning step comprises affixing a pump having means for selectively directing fluid from the first reservoir to the transforming means within the case.

39. The method recited in Claim 40, further comprising affixing a computer within the case and establishing electronic communication between the computer and the mass filter, the computer for controlling data acquisition of the mass filter and for performing analysis of data collected by the mass filter.



40. The method recited in Claim 34, further comprising the step of surrounding the mass filter with a housing and providing a vacuum within the mass filter housing.

41. The method recited in Claim 40, further comprising dissipating heat generated within the case.

42. A method for making a modular, submersible mass spectrometry system comprising a plurality of sealed, substantially fluid-tight pressure vessels for operating in an aqueous environment, the method comprising the steps of:

positioning within a fluidic control pressure vessel:

an inlet from and an outlet to an exterior of the flow injection pressure vessel; and

a pump in fluid communication with a control fluid and a sample fluid, having means for selectively pumping the control fluid and the sample fluid from the to the outlet;

positioning within a mass spectrometer vessel:

an introduction probe in fluid communication with the flow injection pressure vessel outlet for transforming a gas molecule present in fluid therefrom comprising a membrane having selective transport properties for nonpolar volatile compounds, the introduction probe for transforming an analyte molecule present in fluid from the fluidic control pressure vessel outlet from a solution phase into a gas phase;

a fluid line for establishing fluid communication between the fluidic control pressure vessel outlet and the introduction probe;

a linear quadrupole mass filter in fluid communication with the introduction probe for collecting data on the gas-phase analyte molecule; and

5 data analysis means for receiving the data collected by the mass filter and performing an analysis thereof to determine an identity of the gas-phase analyte molecule;

positioning within a pump vessel a vacuum pump for providing low-pressure conditions in the mass filter; and

10 connecting the vacuum pump with the mass filter.

**43.** The method recited in Claim 42, wherein the introduction probe membrane comprises polydimethylsiloxane.

15 **44.** The method recited in Claim 42, further comprising the step of positioning within the fluidic control pressure vessel a means for regulating a temperature of the fluid pumped to the introduction probe.

**45.** The method recited in Claim 42, wherein the data analysis means comprises  
20 a computer in electronic communication with the mass filter having software resident thereon for controlling data acquisition of the mass filter and for performing analysis of data collected by the mass filter.

**46.** The method recited in Claim 42, wherein the vacuum pump comprises two diaphragm pumps connected in series, and further comprising the step of positioning a turbo-molecular drag pump within the mass spectrometer vessel and between the two diaphragm pumps and the mass filter.

5

**47.** The method recited in Claim 42, further comprising the step of positioning a means for dissipating heat generated by the vacuum pump within the pump vessel.

PROFIT-67260